



# 650V Super-junction Power MOSFET

## Description

### 650V Super-junction Power MOSFET


Super-junction power MOSFET is a revolutionary technology for high voltage power MOSFETs, designed according to the SJ principle. The Multi-EPI SJ MOSFET provide an extremely low switching, communication and conduction losses device with highest robustness make especially resonant switching applications more reliable, more efficient, lighter and cooler, designed by Wuxi Unigroup Microelectronics Company.

## Features

- Very low FOM  $R_{DS(on)} \times Q_g$
- 100% avalanche tested
- Easy to use/drive
- RoHS compliant
- Integrated ESD protection diode

## Applications

- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supply (UPS)
- Power Factor Correction (PFC)
- Charger



## Device Marking and Package Information

Device	Package	Marking
TPA65R1K5M	TO-220F	65R1K5M
TPD65R1K5M	TO-252	65R1K5M
TPU65R1K5M	TO-251	65R1K5M
TPY65R1K5MB	SOT-223-2L	65R1K5M

## Key Performance Parameters

Parameter	Value	Unit
$V_{DS} @ T_{j,max}$	700	V
$R_{DS(on),max}$	1.5	$\Omega$
$Q_{g,typ}$	7	nC
$I_D$	3	A
$I_{D,pulse}$	9	A
ESD class (HBM)	1C	
$E_{OSS} @ 400V$	0.79	$\mu J$
Body Diode $d_i/dt$	500	A/ $\mu s$

**Absolute Maximum Ratings  $T_C = 25^\circ\text{C}$ , unless otherwise noted**

Parameter	Symbol	Value	Unit
Continuous Drain Current $T_C = 25^\circ\text{C}$	$I_D$	3	A
$T_C = 100^\circ\text{C}$		1.8	
Pulsed Drain Current (note1)	$I_{D,\text{pulse}}$	9	A
Gate-Source Voltage	$V_{GSS}$	$\pm 20$	V
Single Pulse Avalanche Energy (note2)	$E_{AS}$	26	mJ
Repetitive Avalanche Energy (note2)	$E_{AR}$	0.10	mJ
Avalanche Current	$I_{AR}$	0.6	A
MOSFET dv/dt Ruggedness, $V_{DS} = 0 \dots 480\text{V}$	dv/dt	50	V/ns
Power Dissipation For TO-220F	$P_D$	25	W
Power Dissipation For TO-252,TO-251		28	
Power Dissipation For SOT-223-2L		6.2	
Continuous Diode Forward Current	$I_S$	2.5	A
Diode Pulsed Current (note1)	$I_{S,\text{pulse}}$	33	
Reverse Diode dv/dt (note3)	dv/dt	15	V/ns
Maximum Diode Commutation Speed (note3)	$di_r/dt$	500	A/ $\mu\text{s}$
Operating Junction and Storage Temperature Range	$T_J, T_{stg}$	-55~+150	°C

**Thermal Resistance For TO-220F**

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case	$R_{thJC}$	5	°C/W
Thermal Resistance, Junction-to-Ambient	$R_{thJA}$	80	

**Thermal Resistance For TO-252,TO-251**

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case	$R_{thJC}$	4.4	°C/W
Thermal Resistance, Junction-to-Ambient	$R_{thJA}$	160	

**Thermal Resistance For SOT-223-2L**

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case	$R_{thJC}$	20	°C/W
Thermal Resistance, Junction-to-Ambient	$R_{thJA}$	160	

**Electrical Characteristics**  $T_J = 25^\circ\text{C}$ , unless otherwise noted

Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
<b>Static Characteristics</b>						
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{GS} = 0\text{V}, I_D = 250\mu\text{A}$	650	--	--	V
Zero Gate Voltage Drain Current	$I_{\text{DSS}}$	$V_{DS} = 650\text{V}, V_{GS} = 0\text{V}, T_J = 25^\circ\text{C}$	--	--	1	$\mu\text{A}$
		$V_{DS} = 650\text{V}, V_{GS} = 0\text{V}, T_J = 150^\circ\text{C}$	--	--	100	
Gate-Source Leakage Current	$I_{\text{GSS}}$	$V_{GS} = \pm 20\text{V}$	--	--	$\pm 1$	$\mu\text{A}$
Gate-Source Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	2.5	--	4.0	V
Drain-Source On-State-Resistance	$R_{\text{DS(on)}}$	$V_{GS} = 10\text{V}, I_D = 1.5\text{A}$	--	1.3	1.5	$\Omega$
Gate Resistance	$R_G$	$f = 1.0\text{MHz}$ open drain	--	5.5	--	$\Omega$
<b>Dynamic Characteristics</b>						
Input Capacitance	$C_{\text{iss}}$	$V_{GS} = 0\text{V}, V_{DS} = 100\text{V}, f = 1.0\text{MHz}$	--	225	--	$\text{pF}$
Output Capacitance	$C_{\text{oss}}$		--	10	--	
Reverse Transfer Capacitance	$C_{\text{rss}}$		--	0.4	--	
Total Gate Charge	$Q_g$	$V_{DD} = 560\text{V}, I_D = 3\text{A}, V_{GS} = 10\text{V}$	--	7	--	$\text{nC}$
Gate-Source Charge	$Q_{gs}$		--	1.3	--	
Gate-Drain Charge	$Q_{gd}$		--	3.5	--	
Turn-on Delay Time	$t_{d(\text{on})}$	$V_{DD} = 400\text{V}, I_D = 3\text{A}, R_G = 25\Omega$	--	8.5	--	$\text{ns}$
Turn-on Rise Time	$t_r$		--	7.7	--	
Turn-off Delay Time	$t_{d(\text{off})}$		--	19.0	--	
Turn-off Fall Time	$t_f$		--	16.5	--	
<b>Drain-Source Body Diode Characteristics</b>						
Body Diode Forward Voltage	$V_{SD}$	$T_J = 25^\circ\text{C}, I_{SD} = 1.5\text{A}, V_{GS} = 0\text{V}$	--	0.9	1.2	V
Reverse Recovery Time	$t_{rr}$	$V_R = 400\text{V}, I_F = 3\text{A}, di_F/dt = 100\text{A}/\mu\text{s}$	--	155	--	$\text{ns}$
Reverse Recovery Charge	$Q_{rr}$		--	0.85	--	$\mu\text{C}$
Peak Reverse Recovery Current	$I_{rrm}$		--	11	--	A


**Notes**

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2.  $I_{AS} = 0.6\text{A}, V_{DD} = 50\text{V}, R_G = 25\Omega$ , Starting  $T_J = 25^\circ\text{C}$
3. Identical low side and high side switch with identical  $R_G$




**Typical Characteristics**  $T_J = 25^\circ\text{C}$ , unless otherwise noted


**Figure 1. Output Characteristics**




**Figure 3. On-Resistance vs. Drain Current**




**Figure 5. Gate Charge**




**Figure 2. Transfer Characteristics**



**Figure 4. Capacitance**




**Figure 6. Body Diode Forward Voltage**




**Typical Characteristics**  $T_J = 25^\circ\text{C}$ , unless otherwise noted


**Figure 7. On-Resistance vs. Temperature**




**Figure 8. Breakdown voltage vs. Junction Temperature**




**Figure 9. Transient Thermal Impedance For TO-220F**




**Figure 10. Safe Operation Area For TO-220F**



**Figure 11. Transient Thermal Impedance For TO-252/TO-251**



**Figure 12. Safe Operation Area For TO-252/TO-251**





Typical Characteristics  $T_J = 25^\circ\text{C}$ , unless otherwise noted

Figure 13. Transient Thermal Impedance For SOT-223-2L




Figure 14. Safe Operation Area For SOT-223-2L









Figure 15. Typ. Coss Stored Energy



**Figure A: Gate Charge Test Circuit and Waveform**

**Figure B: Resistive Switching Test Circuit and Waveform**

**Figure C: Unclamped Inductive Switching Test Circuit and Waveform**




## TO-220F




Unit:mm			
Symbol	Min.	Nom	Max.
E	9.96	10.16	10.36
A	4.50	4.70	4.90
A1	2.34	2.54	2.74
A2	0.30	0.45	0.60
A4	2.56	2.76	2.96
c	0.40	0.50	0.65
c1	1.20	1.30	1.35
D	15.57	15.87	16.17
H1	6.70REF		

Unit:mm			
Symbol	Min.	Nom	Max.
e	2.54BSC		
L	12.68	12.98	13.28
L1	2.93	3.03	3.13
ØP	3.03	3.18	3.38
ØP3	3.15	3.45	3.65
F3	3.15	3.30	3.45
G3	1.25	1.35	1.55
b1	1.18	1.28	1.43
b2	0.70	0.80	0.95



## TO-252




Unit:mm			
Symbol	Min.	Nom	Max.
A	2.20	2.30	2.40
A1	0.00	-	0.20
A2	0.97	1.07	1.17
b	0.68	0.78	0.90
b3	5.20	5.33	5.50
c	0.43	0.53	0.63
D	5.98	6.10	6.22
D1	5.30 REF		
E	6.40	6.60	6.80
E1	4.63	-	-

Unit:mm			
Symbol	Min.	Nom	Max.
e	2.286 BSC		
H	9.40	10.10	10.50
L	1.38	1.50	1.75
L1	2.90 REF		
L2	0.51 BSC		
L3	0.88	-	1.28
L4	-	-	1.00
L5	1.65	1.80	1.95
$\theta$	$0^\circ$	-	$8^\circ$



## TO-251




Unit:mm			
Symbol	Min.	Nom	Max.
A	2.20	2.30	2.40
A2	0.97	1.07	1.17
b	0.68	0.78	0.90
b2	0.00	0.04	0.10
b2'	0.00	0.04	0.10
b3	5.20	5.33	5.50
c	0.43	0.53	0.63
D	5.98	6.10	6.22

Unit:mm			
Symbol	Min.	Nom	Max.
D1	5.30 REF		
E	6.40	6.60	6.80
E1	4.63	-	-
e	2.286 BSC		
H	16.22	16.52	16.82
L1	9.15	9.40	9.65
L3	0.88	1.02	1.28
L5	1.65	1.80	1.95



## SOT-223-2L



Unit:mm			
Symbol	Min.	Typ.	Max.
A	1.50	1.60	1.80
A1	0.01	0.06	0.10
B	2.90	3.00	3.10
B1	0.60	0.07	0.80
C	0.22	0.254	0.32
D	6.30	6.50	6.70
E	3.30	3.50	3.70

Unit:mm			
Symbol	Min.	Typ.	Max.
F		4.60	
F1		2.30	
G	0.70	0.90	1.10
H	1.50	1.75	2.00
J	6.70	7.00	7.30
K		0.90	
L	0	0.10	0.20



## Disclaimer

All product specifications and data are subject to change without notice.

For documents and material available from this datasheet, Wuxi Unigroup does not warrant or assume any legal liability or responsibility for the accuracy, completeness of any product or technology disclosed hereunder.

No license, express or implied, by estoppels or otherwise, to any intellectual property rights is granted by this document or by any conduct of Wuxi Unigroup.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling Wuxi Unigroup products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Wuxi Unigroup for any damages arising or resulting from such use or sale.

Wuxi Unigroup disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Wuxi Unigroup's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

Wuxi Unigroup Microelectronics CO., LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

In the event that any or all Wuxi Unigroup products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

Information (including circuit diagrams and circuit parameters) herein is for example only. It is not guaranteed for volume production. Wuxi Unigroup believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.